


Ground Penetrating Radar Training Guide

Principles, Data Interpretation, and Near Surface Applications

A GPR pulse enters the ground and part of it returns

Simplified energy paths through soil and conceptual receiver trace



A transmitted pulse enters the ground; part reflects from a subsurface contrast and returns to the receiver. The receiver records the return at its travel time.

Ground-penetrating radar (GPR) is a geophysical method for investigating contrasts beneath a surface. It does not identify utilities or materials by name. Its value depends on the quality of the recorded response and on how carefully the operator separates observation from interpretation.


The guide explains how radar energy travels through the ground, how responses appear in profiles, how survey geometry and soil conditions affect the data, and what conclusions the method can support. It covers utility investigations and other near-surface applications.

1 What GPR Measures

A GPR antenna transmits short pulses of radio-frequency electromagnetic energy into the ground and records energy that returns to the antenna. A portion of the pulse may reflect when it encounters a boundary where electromagnetic properties change. Other energy continues into the material, scatters in different directions, or is absorbed.

The instrument records the strength and arrival time of returning energy as the antenna moves. It does not take a photograph of an object. The display is a representation of measured responses, shaped by the antenna, the ground, survey geometry, system settings, and processing.

Radar detects contrast, not utilities. A pipe, rock, void, root, buried structure, disturbed soil, or boundary between natural layers can produce a response. The instrument does not determine which of these caused it. Identification requires interpretation and may require supporting information or physical verification.



Simplified view of radar energy interacting with subsurface boundaries.

2 Reflection, Velocity, and Attenuation

Why energy reflects

The ground has electrical properties that influence radar-wave speed and energy loss. When a pulse reaches a boundary with a sufficient change in electromagnetic properties, some energy may reflect. The size and shape of the response depend on the contrast, the boundary geometry, the antenna frequency and orientation, and the amount of energy that reaches the boundary and returns.

A large contrast can produce a strong response, but response strength alone does not identify the feature. A metal object may produce a strong reflection, while a nonmetallic object may also be visible if its surroundings create sufficient contrast. Conversely, an object can be present but produce little recognizable response when its properties are similar to those of the surrounding material or when the return is obscured.

Dielectric properties and radar velocity

The dielectric permittivity of a material affects how quickly radar energy travels through it. Radar energy generally travels faster in air and dry, low-permittivity materials than in wet or higher-permittivity materials. The wave speed is not constant from site to site, and it can vary within a survey area as soil, moisture, pavement, or fill changes.


Electrical conductivity also matters. Conductive ground can dissipate radar energy and reduce the amount that returns from depth. Moisture often increases both the effective permittivity and conductivity of soil; clay-

rich, saline, or saturated materials can therefore slow the wave and attenuate it strongly. The effect depends on the actual ground conditions, not on a soil name alone.

Attenuation and usable depth

Radar energy weakens as it spreads, scatters, and is absorbed. The remaining energy may become too weak or too cluttered to distinguish from background responses. A display that shows a deep time window does not prove that useful energy reached that depth. Increasing display gain can make weak recorded returns easier to see, but it cannot restore energy that was absorbed or never returned.

Drier, less conductive ground may permit greater penetration, while wet clay or saline conditions may limit it severely. These are tendencies, not guarantees. Surface conditions, buried materials, target size, antenna selection, system design, and the survey objective all affect the useful investigation depth.




Changes in layers, moisture, compaction, or backfill can create responses even when no utility is present.

3 From Traces to Radar Profiles

At each antenna position, the system records a trace: returned signal amplitude over a period of time after transmission. As the antenna moves, the system places successive traces beside one another. The resulting cross-section is commonly called a radar profile or B-scan. The horizontal axis represents antenna position along the survey line; the vertical axis represents return time or a depth estimate calculated from an assumed or calibrated wave velocity.

A profile is not a direct underground photograph. Its patterns are produced by measured returns and may be affected by display settings and processing. A single trace shows how the return changes over time at one position; a profile shows how those traces change along a line.



Successive traces form a profile as the antenna moves along a survey line.

Layer reflections and localized targets

Broad, continuous bands may represent boundaries between soil layers, pavement layers, or other laterally continuous changes. A localized reflector crossed by the antenna may form a curved response. The same feature can look different when the antenna crosses it at a different angle, when the ground changes, or when processing and display settings change.

4 Hyperbolas and Survey Geometry

When a survey line crosses a localized reflector, the antenna is farther from the target before and after the closest approach and nearer to it at the closest point. This changing travel path can create a hyperbola in the profile. The shape is a response pattern produced by antenna movement and return time; it is not a picture of the target's physical shape.

For a compact target or a line crossed under suitable geometry, the apex commonly indicates the point of closest approach and is useful for estimating the target position along the survey line. It is not an unconditional guarantee of the target's exact centerline. Antenna offset, target geometry, line angle, depth, processing, and the interaction of nearby features can affect the apparent apex.

A line that crosses a suspected linear feature close to perpendicular often produces a more interpretable response than one that follows alongside it. A parallel pass can produce a stretched, continuous, intermittent, or weak pattern rather than a distinct hyperbola. Diagonal crossings may broaden or skew the response. A second direction helps test whether responses form a plausible alignment and can reveal features that are inconspicuous in one orientation.



The same target can produce different profile patterns when scan direction changes.

A response repeated at consistent positions on crossing or adjacent lines provides stronger evidence of a real subsurface feature than a single isolated indication. Repetition improves interpretation, but it still does not establish the feature's identity, owner, contents, or operating status.

5 Depth Estimates and Calibration

GPR directly records two-way travel time: the time taken for energy to travel from the antenna to a reflecting feature and back. The instrument estimates depth by combining travel time with a wave velocity. In simplified form:

$$\text{Estimated depth} = \text{wave velocity} \times \text{two-way travel time} \div 2$$

Because velocity is an input to the calculation, an incorrect velocity produces an incorrect depth even when the travel time was measured correctly. A dielectric value is commonly used by GPR systems to represent or calculate the selected velocity. The value should match the material conditions as closely as practical.

Calibration can use a known-depth reflector or a suitable hyperbola-fitting method, depending on the system and the available target geometry. Calibration based on a target that is crossed obliquely, poorly resolved, or not correctly identified can introduce error. A value established in one material or moisture condition should not automatically be assumed valid in a different area.

Depth should be reported as an estimate with its basis and limitations. If velocity has not been calibrated, or if conditions vary substantially, the reported depth should be treated as less certain. A displayed number does not remove uncertainty from the assumed ground velocity, antenna footprint, target geometry, or interpretation.

6 Frequency and Antenna Tradeoffs

Antenna frequency influences the balance between resolution and potential penetration. Higher-frequency systems can distinguish smaller, shallower features more clearly under suitable conditions, but their energy is generally attenuated more quickly. Lower-frequency systems may investigate greater depths or larger structures, but they provide coarser resolution and may blend nearby features. Actual performance depends on antenna design, target size, ground conditions, survey setup, and the instrument's processing.

Frequency range	General advantage	General limitation	Typical use
Higher	Greater detail for shallow, small features	Often less usable depth; more affected by attenuation	Concrete, pavement, shallow conduits and reinforcement
Midrange	Practical balance of detail and depth for many near-surface problems	May not resolve very small shallow features or deeper weak contrasts	Utilities, trenches and general near-surface work
Lower	Greater potential depth and response from larger features	Coarser detail; small or closely spaced targets may not separate	Deeper interfaces, large structures and broad subsurface features
Multi-frequency or stepped-frequency	Can provide information at more than one scale	More data and interpretation complexity	Areas with mixed target sizes or uncertain depth needs

These categories are general. Antenna labels, center frequencies, and operating modes vary among systems. Frequency selection is a tradeoff, not a guarantee of a particular depth or resolution.

7 Reading and Enhancing the Display

Gain and filters

Gain changes how recorded amplitudes are displayed. It can make weaker returns more visible, but excessive gain can brighten noise and clutter until meaningful patterns are harder to distinguish. Gain does not increase the energy transmitted into the ground or improve the physical penetration of the survey.

Filters can reduce selected bands of noise or emphasize certain patterns. They can also suppress or reshape useful information. Interpret the original or minimally processed data alongside enhanced views when possible, and do not treat a clearer-looking image as stronger evidence unless the response remains consistent in the underlying data.

Migration and other processing

Processing methods such as migration can reposition dipping energy and collapse a hyperbola toward a likely source location. These methods depend on assumptions, including wave velocity. Incorrect assumptions can distort the result. Processing can help present data, but it cannot identify an unknown object by itself or create information that was never recorded.

A defensible interpretation begins with the observed response: its position, shape, continuity, strength, and repeatability. The operator then considers possible causes and tests them against other survey lines, nearby features, site conditions, records, and independent methods.

8 Common Responses and Possible Causes

Observed response	Possible explanation	Interpretation limit
Repeatable hyperbola at a consistent position	Localized reflector such as a pipe, rock, root, debris, or other object	The curve does not identify the object or prove it is a utility.
Continuous or disrupted horizontal bands	Layer boundaries, pavement interfaces, fill changes, or ringing	A band can be geological or system-related; appearance alone is not material identification.
Linear disturbance or trench-like response	Changed compaction, moisture, backfill, or disturbed layering	The trench may be visible even if the installed pipe is not.
Broad or overlapping arches	Several close reflectors, a large target, clutter, or limited resolution	Do not assume each curve is a separate utility.

Observed response	Possible explanation	Interpretation limit
Very shallow or unusually wide response	Surface metal, fence, pole, tree, overhead wire, direct coupling, or another air-wave source	Inspect the surrounding surface and overhead environment before interpreting it as buried.
Weak or absent response	Low contrast, attenuation, poor coupling, unfavorable orientation, depth, or settings	No recognizable response does not establish that the area is clear.

A trench can create a stronger response than the pipe placed in it. Excavation and backfill change soil structure, compaction, air spaces, and moisture distribution. Those differences may remain detectable after the surface looks restored. The radar is responding to the contrast created by the disturbed zone, not recognizing a trench or identifying the utility inside it.

9 Applications Beyond Utility Investigation

GPR can support many near-surface investigations when materials and conditions provide useful contrast. The method is used to investigate:

- Buried utilities, conduits, and other linear features, especially when survey lines cross suspected alignments in more than one direction.
- Trenches, disturbed soil, voids, and possible loss of support where changes in structure or moisture create a detectable response.
- Soil and pavement layers, shallow geology, and layer thickness when interfaces are continuous and velocity is suitable for depth estimation.
- Concrete and reinforcing systems, with antenna frequency and interpretation matched to the target depth and scale.
- Buried structures, graves, archaeological features, environmental sites, and buried waste, where spatially coherent anomalies can be evaluated by qualified practitioners.
- Bridges, tunnels, walls, embankments, levees, karst features, frozen ground, freshwater, roots, and other near-surface or structural features with appropriate system configuration.

Some specialized applications require equipment, survey design, interpretation skills, and verification beyond general utility locating. A GPR anomaly is evidence of a contrast or feature response; it does not by itself establish the material, purpose, age, or condition of what caused it.

10 Limitations and Evidence-Based Conclusions

GPR performance varies with soil conductivity, moisture, clay content, salinity, surface condition, target depth, target size, target orientation, and the contrast between the target and its surroundings. Reinforcing steel, wire mesh, buried metal, roots, rocks, debris, and closely spaced features can create clutter or mask weaker returns. Rough ground, vegetation, wheel slip, and changing antenna coupling can affect position and trace spacing.

A negative scan means that no recognizable response meeting the stated interpretation criteria was detected within the surveyed area under the conditions and settings used. It does not certify that no buried feature is present. A target may be too deep, too small, too similar to its surroundings, poorly oriented, or obscured by attenuation or clutter.

For utility work, GPR is most useful as one source of evidence. Compare its indications with electromagnetic locating where a conductive path is available, utility records, surface features, access points, and other relevant information. If an excavation decision depends on the identity or precise position of a feature, use an appropriate safe exposure process to verify it. Vacuum excavation may be used where suitable and authorized.

Clear communication separates observation from interpretation. Describe what was measured, where it appeared, whether it repeated, and what conditions limited the survey. State an interpretation as a possibility or probability when the evidence does not establish identity. Report depth as an estimate and state whether velocity was calibrated. The confidence of the conclusion should match the strength of the evidence.

Glossary

A-scan or trace: A record of returned signal amplitude over time at one antenna position.

Attenuation: Reduction of radar energy through spreading, scattering, absorption, or other losses.

B-scan or radar profile: A cross-section formed by arranging traces collected as the antenna moves along a line.

Dielectric permittivity: An electrical property that influences radar-wave velocity and reflection behavior.

Gain: Display amplification applied to recorded amplitudes.

Hyperbola: A curved profile response commonly created as an antenna moves past a localized reflector.

Migration: Processing that moves dipping reflections toward a likely source position using an assumed velocity.

Polarization: The orientation of the transmitted and received electric field, which can affect response to linear targets.

Reflection: Radar energy returned from a boundary or feature with sufficient electromagnetic contrast.

Resolution: The ability to distinguish small features or separate nearby responses.

Two-way travel time: Elapsed time for radar energy to travel to a reflector and return to the antenna.

Velocity: The speed of radar energy through a material; used with travel time to estimate depth.